

```

[0x080485a4]> pdf @ sym.read_valid_int
/ (fcn) sym.read_valid_int 76
|   sym.read_valid_int (int arg_8h, int arg_ch);
|       ; var int local_ch @ ebp-0xc
|       ; arg int arg_8h @ ebp+0x8
|       ; arg int arg_ch @ ebp+0xc
|       ; CALL XREF from 0x080484ef (main)
|       0x0804848b      55          push ebp
|       0x0804848c      89e5      mov ebp, esp
|       0x0804848e      83ec18     sub esp, 0x18
|       0x08048491      c745f4000000. mov dword [local_ch], 0      ;->int x=0 en dirección ebp-0xc
|   ..-> 0x08048498      83ec04     sub esp, 4
|   :: 0x0804849b      ff750c     push dword [arg_ch]
|   :: 0x0804849e      ff7508     push dword [arg_8h]
|   :: 0x080484a1      68c0850408 push str.Provide_a_number_x_between__d_and__d: ; 0x80485c0 ; "Provide a number x between %d and
% d: "
|   :: 0x080484a6      e895feffff     call sym.imp.printf          ; int printf(const char *format)
|   :: 0x080484ab      83c410     add esp, 0x10
|   :: 0x080484ae      83ec08     sub esp, 8
|   :: 0x080484b1      8d45f4     lea eax, [local_ch]
|   :: 0x080484b4      50          push eax
|   :: 0x080484b5      68e7850408 push 0x80485e7
|   :: 0x080484ba      e8b1feffff     call sym.imp.__isoc99_scanf      ;->scanf
|   :: 0x080484bf      83c410     add esp, 0x10
|   :: 0x080484c2      8b45f4     mov eax, dword [local_ch]      ;->guarda valor de x en eax
|   :: 0x080484c5      394508     cmp dword [arg_8h], eax      ; [0x13:4]=-1 ; 19      ;->min < x
|   `==< 0x080484c8      7fce      jg 0x8048498
|   : 0x080484ca      8b45f4     mov eax, dword [local_ch]      ;->guarda valor de x en eax
|   : 0x080484cd      3b450c     cmp eax, dword [arg_ch]      ; [0xc:4]=-1 ; 12      ;->x > max
|   `=< 0x080484d0      7fc6      jg 0x8048498
|       0x080484d2      8b45f4     mov eax, dword [local_ch]
|       0x080484d5      c9          leave
|       0x080484d6      c3          ret
\

```